

DUCTING

QUADROFLEX - OVALIZED FLEXIBLE DUCT

Australian Standard (AS) 4254

Fire Rated Flexible Duct

OVAL UNILOK FR1 & OVAL UNILOK S Suitable for all HVAC Systems

OVAL QS-FLEX Suitable for Ducted Evaporative Systems Only


QUADROFLEX has been specifically designed to fit into false ceilings, between floors and low ground clearance applications. Refer to pages A4-A6 for individual duct compositions. Operating temperature of -10°C to +80°C. (UNILOK-S & UNILOK FR1 only).



EQUIVALENT ROUND DUCT SIZE	WIDTH	HEIGHT
200	260	140
250	325	160
300	380	200
350	435	240
400	470	310
450	555	320

← WIDTH →

↑ HEIGHT ↓



N.B. Add approximately 60-120mm to these sizes to allow for insulation.

» ORDERING EXAMPLE

EXAMPLE 1: Insulated R^T0.6 QUADRO UNILOK FR1 10" **991711103**

EXAMPLE 2: Insulated R^T1 QUADRO UNILOK-S 18" **991654183**

EQUIVALENT ROUND DUCT SIZE	QUADRO UNILOK FR1		QUADRO UNILOK-S	
	CODE PREFIX		CODE PREFIX	
	R ^T 0.6	R ^T 1	R ^T 0.6	R ^T 1
8				
10				
12				
14				
16				
18				

* Non acoustic supplied standard (acoustic available upon request).

* 3 meter lengths only.

* Pricing and availability on QUADRO Q/S FLEX on application.

* Oval joiners available refer page B9.

All prices **DO NOT** include GST.

www.westaflex.com.au