

November 2011

Insulation for Flexible Ducting

Autex Pty offers the following products for use as insulation in Flexible Ducting.

R 0.45 - 40mm - 180gsm

R 0.6 - 40mm - 220gsm

R0.85 - 60mm - 380gsm

R 1.0 - 60mm - 420gsm

R 1.25 - 80mm - 420gsm

R 1.5 - 90mm - 750gsm

R2.0 - 100mm -1400gsm

R2.4 - 110mm - 2100gsm

These R Ratings are as measured ex manufacture. Prolonged compression, packaging or stretching of the product will be detrimental to the final R Rating of any Duct produced.

Whilst other weights of Polyester insulation are available for use in flexible ducting, no warranty in regards to thermal performance will be given for these products.

For more information and pricing please contact your Autex representative.

Kind Regards

Robert Jones
Sales & Development Manager
Autex Pty Ltd.

AUTEX



Autex Pty Ltd

166 Bamfield Rd, PO Box 5099,
West Heidelberg, Melbourne,
VIC 3081 Australia
Phone +61 3 9457 6700
Fax +61 3 9457 1020

Freephone 1800 678 160
www.autex.com.au

ISO 9001 CERTIFIED
ISO 14001 CERTIFIED
ABN 84 495 094 585